

# CAVABRASIVO 6 T11



Suction and delivery hose suitable for abrasive products dry or mixed with water.

## DESCRIPTION

### Tube

NR-SBR, black, conductive

### Reinforcement

synthetic plies, steel wire helices, a/s copper wire to discharge static electricity

### Cover

smooth, black, conductive, cloth finish. Abrasion, ageing and ozone resistant

## TECHNICAL CHARACTERISTICS

**Temperature range :** -40°C / +70°C ( -40°F / +158°F )

**Norms :** ISO 1307 for dimensional tolerances

Inside diameter		Outside diameter		Length		Vacuum		Working pressure		Burst pressure		Appr. weight		Bending radius	
[mm]	[in]	[mm]	[in]	[mt]	[ft]	[bar]	[psi]	[bar]	[psi]	[bar]	[psi]	[kg/mt]	[lbs/ft]	[mm]	[in]
51	2,00	64	2,51	40	130	0,9	13	6	87	18	260	1,60	1,07	200	7,87
76	3,00	91	3,60	40	130	0,9	13	6	87	18	260	2,79	1,87	300	11,81
90	3,54	105	4,13	40	130	0,9	13	6	87	18	260	3,33	2,23	360	14,17
100	3,93	116	4,56	40	130	0,9	13	6	87	18	260	3,76	2,52	400	15,74
102	4,00	119	4,68	40	130	0,9	13	6	87	18	260	4,12	2,76	400	15,74
127	5,00	146	5,74	40	130	0,8	11,5	6	87	18	260	5,65	3,79	610	24,00
152	6,00	173	6,81	40	130	0,8	11,5	6	87	18	260	8,80	5,91	760	29,92
200	7,87	227	8,93	40	130	0,8	11,5	6	87	18	260	13,68	9,19	1015	40,00
203	8,00	230	9,05	20	65	0,8	11,5	6	87	18	260	14,39	9,66	1015	40,00
305	12,00	341	13,42	12	39	0,8	11,5	6	87	18	260	26,11	17,54	1950	76,77

Data refer to ambient temperature (20°C). Other diameters, wall thickness and pressure only on specific request.