

## DRYFOOD ANTISTATIC D



### TECHNICAL CHARACTERISTICS

**Temperature range :** -25°C / +80°C ( -13°F / +176°F )

**Norm :** ISO 1307 for dimensional tolerances



Delivery hose suitable for powdery and granular dry food products.

### DESCRIPTION

#### Tube

NBR, white, antistatic ( $R < 10^9 \Omega/m$ ), phthalates free, tested in compliance with 1907/2006/CE (REACH). Meets FDA 21 CFR 177.2600, BFR recommendation XXI cat 4, DM 21.03.73 e seguenti, EUROPEAN REGLEMENT 1935/2004/CE

#### Reinforcement

synthetic plies, on request a/s copper wires to discharge static electricity

#### Cover

smooth, black, conductive, abrasion, ageing and ozone resistant, cloth finish

#### Sterilization

refer to guidelines for cleaning and sanitizing on Tudertechnica website

#### Marking

TUDERTECHNICA DRYFOOD ANTISTATIC

Inside diameter		Outside diameter		Working pressure		Burst pressure		Appr. weight		Bending radius	
[mm]	[in]	[mm]	[in]	[bar]	[psi]	[bar]	[psi]	[kg/mt]	[lbs/ft]	[mm]	[in]
51	2,00	66	2,60	6	90	18	270	1,82	1,22	-	-
76	3,00	94	3,70	6	90	18	270	3,22	2,16	-	-
102	4,00	124	4,88	6	90	18	270	5,06	3,39	-	-
127	5,00	151	5,94	6	90	18	270	7,13	4,78	-	-
152	6,00	176	6,93	6	90	18	270	8,43	5,65	-	-

Other diameters, wall thickness and pressure only on specific request. Data refer to ambient temperature (20°C).