

TUCHEM® UPE CHIPS FULL CONDUCTIVE



SMOOTH, BLACK, CONDUCTIVE,
CLOTH FINISH EPDM
GALVANIZED WIRE HELICES
SYNTHETIC PLIES
WHITE UPE WITH CONDUCTIVE CHIPS

TECHNICAL CHARACTERISTICS

Temperature range : -35°C / +100°C (-31°F / +212°F)

The operating temperature of the hose is directly dependent upon the specific fluid been conveyed and the length of time the fluid is in contact with the hose.

Electrical properties : type Ω/T according to norm EN 12115 (R<10⁶ Ω, R<10⁹ Ω through the hose wall)

Norm : EN12115 - TRbF 131/2



Suction and delivery hose designed according to EN 12115 standards for chemical products.

DESCRIPTION

Tube

UPE, white with conductive chips, phthalates free, tested in compliance with 1907/2006/CE (REACH). Meets FDA 21 cfr 177.1520, BfR Cat III, DM 21.03.73 e seguenti, EUROPEAN REGLEMENT 1935/2004/CE

Reinforcement

synthetic plies, galvanized wire helices, a/s wire to discharge static electricity

Cover

smooth, EPDM, black, conductive, abrasion, ageing and ozone resistant, cloth finish

Sterilization

refer to guidelines for cleaning and sanitizing on Tudertechnica website

Marking

white/blue tape

TUDERTECHNICA TUCHEM® UPE CHIPS FULL CONDUCTIVE

embossed according to norm EN 12115

TUDERTECHNICA UHMWPE EN12115:2011 DN SD PN 16 BAR Ω /T Q/Y

Inside diameter		Outside diameter		Vacuum		Working pressure		Burst pressure		Appr. weight		Bending radius	
[mm]	[in]	[mm]	[in]	[bar]	[psi]	[bar]	[psi]	[bar]	[psi]	[kg/mt]	[lbs/ft]	[mm]	[in]
19	0,75	31	1,22	0,9	13	16	250	64	1000	0,75	0,50	115	4,53
25	1,00	37	1,46	0,9	13	16	250	64	1000	0,92	0,62	155	6,10
32	1,25	44	1,73	0,9	13	16	250	64	1000	1,10	0,74	200	7,87
38	1,50	51	2,00	0,9	13	16	250	64	1000	1,39	0,93	240	9,45
50	1,97	66	2,60	0,9	13	16	250	64	1000	2,30	1,54	330	12,99
51	2,00	67	2,64	0,9	13	16	250	64	1000	2,33	1,56	330	12,99
63,5	2,50	79,5	3,13	0,9	13	16	250	64	1000	3,09	2,07	415	16,34
75	2,95	91	3,58	0,9	13	16	250	64	1000	3,58	2,40	500	19,69
76	3,00	92	3,62	0,9	13	16	250	64	1000	3,62	2,42	500	19,69
100	3,94	116	4,57	0,9	13	12	185	48	750	4,63	3,10	675	26,57
102	4,00	118	4,65	0,9	13	12	185	48	750	4,67	3,13	675	26,57

Data refer to ambient temperature (20°C).