



## TUCHEM® UPE



SMOOTH, BLACK, CONDUCTIVE,  
CLOTH FINISH EPDM

GALVANIZED WIRE HELICES

SYNTHETIC PLYS

TRANSLUCENT UPE

### TECHNICAL CHARACTERISTICS

**Temperature range :** -35°C / +100°C (-31°F / +212°F)

The operating temperature of the hose is directly dependent upon the specific fluid been conveyed and the length of time the fluid is in contact with the hose.

**Electrical properties :** type Ω/T according to norm EN 12115 (R<10<sup>6</sup> Ω)

**Norm :** EN12115 - TRbF 131/2



Suction and delivery hose designed according to EN 12115 standards for chemical products.

### DESCRIPTION

#### Tube

UPE, translucent. Phthalates free, tested in compliance with 1907/2006/CE (REACH). Meets FDA 21 CFR 177.1520, BfR Cat III, DM 21.03.73 e seguenti, EUROPEAN REGLEMENT 1935/2004/CE AND 10/2011/CE, JAPAN-Ministry of Health and Welfare Notice No.370,1959 and No.201,2006

#### Reinforcement

synthetic plies, galvanized wire helices, a/s copper wire to discharge static electricity

#### Cover

smooth, EPDM, black, conductive, abrasion, ageing and ozone resistant, cloth finish

#### Sterilization

refer to guidelines for cleaning and sanitizing on Tudertechnica website

#### Marking

white/blue tape

TUDERTECHNICA TUCHEM® UPE

embossed according to norm EN 12115

TUDERTECHNICA UHMWPE EN12115:2011 DN SD PN 16 BAR Ω Q/Y

Inside diameter		Outside diameter		Vacuum		Working pressure		Burst pressure		Appr. weight		Bending radius	
[mm]	[in]	[mm]	[in]	[bar]	[psi]	[bar]	[psi]	[bar]	[psi]	[kg/mt]	[lbs/ft]	[mm]	[in]
19	0,75	31	1,22	0,9	13	16	250	64	1000	0,75	0,50	115	4,53
25	1,00	37	1,46	0,9	13	16	250	64	1000	0,92	0,62	155	6,10
32	1,25	44	1,73	0,9	13	16	250	64	1000	1,10	0,74	200	7,87
38	1,50	51	2,00	0,9	13	16	250	64	1000	1,39	0,93	240	9,45
50	1,97	66	2,60	0,9	13	16	250	64	1000	2,30	1,54	330	12,99
51	2,00	67	2,64	0,9	13	16	250	64	1000	2,33	1,56	330	12,99
63,5	2,50	79,5	3,13	0,9	13	16	250	64	1000	3,09	2,07	415	16,34
75	2,95	91	3,58	0,9	13	16	250	64	1000	3,58	2,40	500	19,69
76	3,00	92	3,62	0,9	13	16	250	64	1000	3,62	2,42	500	19,69
100	3,94	116	4,57	0,9	13	12	185	48	750	4,63	3,10	675	26,57
102	4,00	118	4,65	0,9	13	12	185	48	750	4,67	3,13	675	26,57

Data refer to ambient temperature (20°C).